

Superbike and Endurance

		Tyre Size	Tread Pattern	Soft	Medium	Strong	Hard	Recommended Rim width	Permitted Rim Widths	Overall Diameter	Overall Width	Shoulder Diameter	Inflation Pressures		
													Cold	80C Warmers	Hot Running
16" Front	Dry	130/65R16	KR106	6614	6704	6680		3.50"	3.35" - 3.85"	605 mm	124 mm	505 mm	2.1	2.3	2.4 - 2.6
	Wet	130/65R16	KR191	414				3.50"	3.35" - 3.85"	605 mm	124 mm	505 mm	2.2		
16.5" Front	Dry	125/80R420	KR106	6614	6704	6680	6671	3.50"	3.35" - 3.75"	603 mm	121 mm	505 mm	2.1	2.3	2.4 - 2.6
		125/80R420	KR191	414				3.50"	3.35" - 3.75"	603 mm	121 mm	505 mm	2.2		
17" Front	Dry	125/80R17	KR106	6614	6704	6680	6671	3.50"	3.35" - 3.75"	606 mm	116 mm	507 mm	2.0 - 2.1	2.3	2.4 - 2.6
	Intermediate	125/80R17	KR394	TbA				3.50"	3.35" - 3.75"	606 mm	116 mm	507 mm	2.0 - 2.1	2.3	2.4 - 2.6
	Wet	125/80R17	KR191	414				3.50"	3.35" - 3.75"	606 mm	116 mm	507 mm	2.2		
16.5" Rear	Dry	200/65R420	KR108	7614	7704	6680		6.25"	6.00" - 6.25"	662 mm	200 mm		1.2 - 1.5	1.3	1.4 - 1.6
	Wet	195/80R420	KR392	414	3701			6.25"	6.00" - 6.25"	654 mm	192 mm	533 mm	1.9 - 2.2		
17" Rear	Dry	195/65R17	KR108	7614	7704	6680		6.00"	5.50" - 6.00"	656 mm	191 mm	518 mm	1.2 - 1.5	1.3	1.4 - 1.6
	Intermediate	195/70R17	KR395	899	523			6.00"	5.50" - 6.00"	657 mm	190 mm	540 mm	1.7 - 1.9	2.2	2.2 - 2.4
	Wet	195/70R17	KR390	414	3701			6.00"	5.00" - 6.00"	657 mm	190 mm	540 mm	1.9 - 2.2		

Supersport (600cc)

		Tyre Size	Tread Pattern	Soft	Medium	Strong	Hard	Recommended Rim width	Permitted Rim Widths	Overall Diameter	Overall Width	Shoulder Diameter	Inflation Pressures		
													Cold	80C Warmers	Hot Running
Front	Dry	120/70ZR17	D211F GP	6614	6704	6680		3.50"	3.35" - 3.75"	606 mm	116 mm	507 mm	2.0 - 2.1	2.3	2.4 - 2.6
	Wet	125/80R17	KR191	414				3.50"	3.35" - 3.75"	606 mm	116 mm	507 mm	2.2		
Rear	Dry	190/55ZR17	D211 GP	7614	7704	6680		5.50"	5.00" - 6.00"	649 mm	190 mm	530 mm	1.2 - 1.5	1.3	1.4 - 1.6
	Wet	190/55ZR17	KR393	414	3701			5.50"	5.00" - 6.00"	649 mm	190 mm	530 mm	1.9 - 2.0		

Superstock (1,000cc)

		Tyre Size	Tread Pattern	Soft	Medium	Strong	Hard	Recommended Rim width	Permitted Rim Widths	Overall Diameter	Overall Width	Shoulder Diameter	Inflation Pressures		
													Cold	80C Warmers	Hot Running
Front	Dry	120/70ZR17	D211F GP	6614	6704	6680		3.50"	3.35" - 3.75"	606 mm	116 mm	507 mm	2.0 - 2.1	2.3	2.4 - 2.6
	Wet	125/80R17	KR191	414				3.50"	3.35" - 3.75"	606 mm	116 mm	507 mm	2.2		
Rear	Dry	200/55ZR17	D211 GP	7614	7704	6680		6.00"	5.50" - 6.00"	656 mm	191 mm	518 mm	1.2 - 1.5	1.3	1.4 - 1.6
	Wet	195/70R17	KR390	414	3701			6.00"	5.00" - 6.00"	657 mm	190 mm	540 mm	1.9 - 2.2		

Super Moto

		Tyre Size	Tread Pattern	Compounds V Soft	Soft	Medium		Recommended Rim width	Permitted Rim Widths	Overall Diameter	Overall Width	Shoulder Diameter	Inflation Pressures		
													Cold	80C Warmers	Hot Running
16.5" Front	Dry	125/80R420	KR106	417	950			3.50"	3.35" - 3.75"	603 mm	121 mm	505 mm			
	Wet	125/80R420	KR188/a	417				3.50"	3.35" - 3.75"	603 mm	121 mm	505 mm			
17" front	Dry	125/80R17	KR106	417	950			3.50"	3.35" - 3.75"	606 mm	116 mm	507 mm			
	Wet	120/70R17	KR222	WA				3.50"	3.35" - 3.75"						
17" Rear	Dry	170/55R17	KR108		950	237 / 523		5.50"	5.00" - 5.50"	628 mm	161 mm	509 mm	1.5 - 1.8		
	Wet	165/50R17	KR244	WA											

125cc Road Race

		Tyre	Tread					Recommened	Permitted	Overall		Shoulder	Inflation Pressures		
		Size	Pattern	Soft	Medium	Strong	Hard	Rim width	Rim Widths	Diameter	Width	Diameter	Cold	80C Warmers	Hot Running
Front	Dry	95/70R17	KR149	B	C	D	H	2.50"	2.50"	576 mm	88 mm		1.7 - 1.8	2.0	2.0 - 2.1
	Wet	95/70R17	KR189	WA				2.50"	2.50"	576 mm	88 mm		1.9 - 2.0		
Rear	Dry	115/70R17	KR133	B	C	D	H	3.50"	3.50"	601 mm	115 mm		1.8 - 1.9	2.0 - 2.1	2.1 - 2.2
	wet	115/70R17	KR389	WA				3.50"	3.50"	600 mm	117 mm		2.0 - 2.1		

250cc Road Race

		Tyre	Tread					Recommened	Permitted	Overall		Shoulder	Inflation Pressures		
		Size	Pattern	Soft	Medium	Strong	Hard	Rim width	Rim Widths	Diameter	Width	Diameter	Cold	80C Warmers	Hot Running
Front	Dry	125/80R17	KR106	6614	6704	6680	6671	3.50"	3.35" - 3.75"	606 mm	116 mm	507 mm	2.0 - 2.1	2.3	2.4 - 2.6
	Wet	125/80R17	KR191	414				3.50"	3.35" - 3.75"	606 mm	116 mm	507 mm	2.2		
Rear	Dry	165/55R17	KR108	3178	3704	3751		5.50"	5.00" - 5.50"	628 mm	162 mm	509 mm	1.7 - 1.9	2.2	2.20 - 2.40
	Wet	165/55R17	KR393	414	3701			5.50"	5.00" - 5.50"	628 mm	162 mm	509 mm	2.2		

Classic Tyres

		Tyre	Tread					Recommened	Permitted	Overall		Shoulder	Inflation Pressures		
		Size	Pattern	Soft	Medium	Strong	Hard	Rim width	Rim Widths	Diameter	Width	Diameter	Cold	80C Warmers	Hot Running
Front	< 250cc	2.75/3.75-18	KR825	950				WM 2	WM 1 - WM 3						
Front	>250cc	3.50/3.25-18	KR124/a	950	523			WM 3	WM 2 - 2.50"						
Rear	< 350cc	3.50-18	KR124		523			WM 3	WM 2 - 2.50"						
Rear	250 - 350cc	3.75/5.00-18	KR164		523			3.00"	2.50" - 3.00"						
Rear	500 - 1,000cc	3.75/6.00-18	?		523			3.50"	3.00" - 4.00"						
Front		3.00-19	KR76			TbC									
Universal		3.50-19	KR73			TbC									
Universal	Sidecar	3.50-16	RS 2				TbC								